



ADVAMASTIC

ACRYLIC BASED JOINT MASTIC

DESCRIPTION

ADVAMASTIC is a general purpose one-pack acrylic joint mastic and crack repair filler, for interior and exterior use. It forms a water resistant joint sealant in situations too demanding for normal mastic.

USES

- ▶ Between tile and concrete elements
- ▶ Around doors and windows
- ▶ Behind skirting and architraves
- ▶ To repair cracks in plaster and concrete
- ▶ For concrete slabs and tiles

ADVANTAGES

- ▶ Waterproof
- ▶ Weather resistant
- ▶ Permanent flexibility ($\pm 15\%$) of original joint size
- ▶ Easy to apply
- ▶ High adhesion to most building surfaces
- ▶ Can be painted after 24 hours
- ▶ Economical

APPLICATION

PREPARATION OF JOINTS

- ▶ Ensure that all dust, dirt and foreign matter are brushed and scrapped away.
- ▶ Also ensure the joint is solid, free from salts, oil, grease and ridges.
- ▶ Clean aluminum surfaces with white spirit.
- ▶ On firm, dust free surfaces the use of primer is not necessary.
- ▶ For surfaces that show signs of constant dusting or flaking, or for joints where constant high movement is anticipated. Use suitable back up rod to reduce joint depth to $<10\text{mm}$.
- ▶ For exterior areas, do not apply if rain is imminent. Ensure at least 48 hours of dry condition.

ADVAMASTIC can be applied by hand or caulking gun. Ensure that the sealant is pushed firmly into the joint completely filling the area. Any tooling of the sealant surface must be carried out immediately using a joint shaping tool soaked in detergent solution. Edges of the joints should be protected with masking tape to avoid application. The tapes should be removed immediately after tooling.



ADVAMASTIC

ACRYLIC BASED JOINT MASTIC

COVERAGE

1Kg will fill 4.5 linear meter of a joint size 10mm(depth) x 15mm(width).

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant Material Safety Data Sheet.

CLEANING

Tools use for ADVAMASTIC should be cleaned with water directly after use.

TECHNICAL SPECIFICATIONS

Product	Ready-mixed acrylic joint mastic
Binders	Acrylic copolymer
Fillers	Fine precisely graded fillers
Dilution	With water if required
Specific Gravity	1.50
Drying Time	Surface dry <2 hours at 35°C and 65% R.H. Hard dry (at 10mm thickness) approx. 5 days at 35°C and 85% R.H.
Color	White, Grey or As Requested
Expansion	±15% of original joint width
Age Resistance	Excellent
Toxicity	Non-toxic
Storage	Should be stored in dry places and at temperature of 5-25°C.
Shelf Life	12 months in clean frost-free condition and in unopened container.
Packing	20Kg/Pail

The information given in this datasheet is based on both current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we cannot accept responsibility for any work carried out with our materials as we have no control over methods of application, site, conditions, etc.